

Questionnaire for manhole cover SD2

Project: _____

Customer: _____ Person in charge: _____ Phone: _____

Site: _____ Customer No.: _____ Fax: _____

☐ Offer Offer No.: _____ Price per unit: _____ €,☐ Order Order No.: _____ Manufacturing costs per unit: _____ €, Item.: _____, Q: **P** _____**Short text: Manhole cover SD2, rain-proof, completely made of stainless steel****1. Material:**☐ 1.4307 (AISI 304 L)☐ 1.4404 (AISI 316 L)**2. Clear shaft opening:**Diameter \varnothing = _____ mm

Please note: \varnothing one part: min. 600 mm, max. 1300 mm
 \varnothing two part: min. 1200 mm, max. 2000 mm

3. Design:☐ one-part☐ two part (The sealing is standardly on the bottom side of the cover in the two-part version!)☐ Cross bar rigidly welded, not removeable☐ Cross bar screwed, removeable (clear opening is reduced by 180 mm)☐ Cross bar hinged**4. Frame:**☐ Frame for concrete setting with wall clamps☐ SD2.1 $\varnothing < 1100$ mm: Frame designed for bolted fixing with doweling clips, Width: 40 mm, Height: 40 mm☐ SD2.1 $\varnothing < 1100$ mm: Frame designed for bolted fixing with doweling clips, Width: 40 mm, Special height: _____ (max. 300mm)☐ SD2.1 $\varnothing \geq 1100$ mm: Frame designed for bolted fixing with doweling clips, Width: 50 mm, Height: 50 mm☐ SD2.1 $\varnothing \geq 1100$ mm: Frame designed for bolted fixing with doweling clips, Width: 50 mm, Special height: _____ (max. 300mm)☐ SD2.2 Frame designed for bolted fixing with doweling clips, Width: 50 mm, Height: 50 mm☐ SD2.2 Frame designed for bolted fixing with doweling clips, Width: 50 mm, Special height: _____ mm (max. 300 mm)☐ Special length of doweling clips: _____ mm (top of channel up to bore axis: min. 105 mm, max. 300 mm)☐ Frame designed for bolted fixing throught the frame, Width: 80 mm, Height: 60 mm☐ with lift-off safety device☐ without lift-off safety device☐ Frame designed for bolted fixing throught the frame, Width: 80 mm, Special height: _____ mm (max. 300 mm)☐ with lift-off safety device☐ without lift-off safety device

5. Insulation and vapour hood:

- a) ☐ insulation of the cover ☐ special insulation height of the cover : _____ mm (max. 50 mm)
☐ insulation of the frame

- b) ☐ vapour hood DN 150, centrally welded

For multi-part covers:

- ☐ vapour hood on all cover parts ☐ vapour hood only left side ☐ vapour hood only right side

6. Optional equipment:

- ☐ Opening possibility from below
☐ Cover plate, 4 mm, with handle
☐ Handle
☐ Magnetic contact (cover open/closed indicator)
☐ Detachable hinges, i. e. removable cover
☐ Sealing on the bottom side of the cover (Standardly by multi-part covers)
☐ Cover which can only be opened from below (with locking lever, without upper locking part)
☐ Paint RAL colour: _____
☐ Biofilter in vapour hood (only DN 150) (odour elimination) *or*
(Info: retrofitting biofilter only possible with insulated covers)
☐ Energy self-sufficient wind-powered ventilator
☐ Cover on the top of the wall executed according to customer's structural drawing (Not with frame for setting in concrete)
Width of the on-site wall crown: ____ mm / Frame bending downwards: ____ mm

7. Locking System:

- ☐ Screw lock (instead of self-retracting lock)
(Note: For two-part covers, 2 screw locks per individual cover part as standard, for hinged cross bar, 2 screw locks in the opening cover.)
☐ Huber - Passavant-lock
☐ Fireservice-lock

☐ KABA – locking system Switzerland standard
☐ DENY – locking system French standard

8. Other accessories/Comments:

.....

.....

.....

.....

9. Sales person in charge:

..... Phone No.: +498462/201-____ Fax No.: +498462/201-399 E-mail:____@huber.de

10. Enclosures for the design engineers:

- ☐ Drawing ☐
- ☐ Photo ☐

Safety lock and mounting set has to be recorded as a separate item:

Safety lock for increased security with self-retracting lock SD2

- | | |
|--|---|
| ___ X <input type="checkbox"/> 300379 – SSS 35mm noPZ noISO Price: € | Mounting material SD2 |
| ___ X <input type="checkbox"/> 301384 – SSS 35mm noPZ ISO Price: € | ___ X <input type="checkbox"/> 706934 Bef.-Mat. bis 1000x1000 Price: € |
| ___ X <input type="checkbox"/> 301385 – SSS 35mm HHB1 noISO Price: € | ___ X <input type="checkbox"/> 706943 Bef.-Mat. bis 1000x1000 ILLMOD Price: € |
| ___ X <input type="checkbox"/> 301386 – SSS 35mm HHB2 noISO Price: € | ___ X <input type="checkbox"/> SPECIAL – Bef.-Mat. (Serviceartikel) Price: € |
| ___ X <input type="checkbox"/> 301387 – SSS 35mm HHB3 noISO Price: € | Safety lock for SD2 with screw lock |
| ___ X <input type="checkbox"/> 301388 – SSS 35mm HHB4 noISO Price: € | ___ X <input type="checkbox"/> 301874-SSS 35mm noPZ Price: € |
| ___ X <input type="checkbox"/> 301544 – SSS 35mm HHB1 ISO Price: € | ___ X <input type="checkbox"/> 301875-SSS 35mm HHB1 Price: € |
| ___ X <input type="checkbox"/> 301545 – SSS 35mm HHB2 ISO Price: € | ___ X <input type="checkbox"/> 301876-SSS 35mm HHB2 Price: € |
| ___ X <input type="checkbox"/> 301546 – SSS 35mm HHB3 ISO Price: € | ___ X <input type="checkbox"/> 301877-SSS 35mm HHB3 Price: € |
| ___ X <input type="checkbox"/> 301547 – SSS 35mm HHB4 ISO Price: € | ___ X <input type="checkbox"/> 301878-SSS 35mm HHB4 Price: € |
| ___ X <input type="checkbox"/> 10238266 pollen filter, 1.4404, (exchangeable) in vapour hood DN 150 Price: € | |